

YOUR AUTOMOTIVE LIGHTING PARTNER

AUTOMOTIVE LIGHTING SYSTEM



NINGBO NOVA TECHNOLOGY CO., LTD.

- ⋈ Email: info@novavehicle.com
- Tel/Wechat/WhatsApp: 086-150 8841 5393
- Wed: www.novavehicle.com
- Office Add.: The North of Tiantong Road 1539#, YinZhou, Ningbo







ABOUT US

Ningbo Nova Technology Co., Ltd. is a leading emergency warning light supplier with 16+ years of expertise in the automotive vehicle lighting industry. Driven by innovation, we continuously push boundaries to deliver cutting-edge solutions that meet the evolving demands of global markets.

Dedicated to collaborative partnerships, we provide comprehensive OEM and ODM services for both the aftermarket and original equipment manufacturers. Beyond being a supplier, we strive to become your strategic ally, committed to shared growth and excellence.



With a strong focus on research and development, we maintain a team of senior engineers specializing in optical, structural, and electronic engineering disciplines. While our core expertise lies in LED warning light systems, we additionally offer comprehensive customization services encompassing optical components, PCBA, wiring harnesses, as well as both plastic housing and aluminum die-casting solutions.

OEM and ODM Service

 With extensive expertise in OEM and ODM services, NOVA delivers tailored lighting solutions—from minor bezel modifications to fully custom light designs. We provide flexible options, including cost-effective and premium-tier solutions, ensuring a reliable partnership for projects of any scale.

Completely Vehicle Lighting Solution

 As a full-service vehicle lighting solutions provider, we optimize procurement ecosystems to deliver cost efficiencies while creating sustainable value for all stakeholders.


To be Your Partner, Not Only a Supplier

 NingBo NOVA Vehicle aspires to build strategic partnerships in the automotive lighting industry.
 We go beyond being a supplier - we aim to become your trusted partner and your extended operational arm in China.

















QUALITY CONTROL

IN-HOUSE &OUTSIDE TESTING







Optical Integrating

ECE R65









Waterproof Machine

Salty-Corrosion Machine

Machine Machine

Hi-Low Temp





Anti-Dust

Machine





LED WARNING LIGHT

05

LED LIGHTBAR

LED LIGHTHEAD

HIDEAWAY LIGHT

LED BEACON

VISOR LIGHT

CONTROLLER

SPEAKER&SIREN

AUXILIARY LIGHT

51

LED STRIP LIGHT

LED CEILING LIGHT

CARAVAN LIGHT

LED WORK LIGHT

LED SIGNAL LIGHT

SPARE PARTS 62



NOVA

• LED LIGHTBAR NV-LB










- Available in single and dual colors.
- 16", 24", 31",40", 48", 55", 63" and 70" for your options.
- Bespoke your lightbar with takedown light, alley light, traffic arrow light, cruise light and dimming function.
- Streamline design makes the light intensity is more uniform and more powerful.
- Black housing for amber market and colorful housing for blue market.
- Available with our controller SC5X or SC7X.
- The modules and PCB design with connector, easy to repair and maintenance.











ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	WIRE	APPROVAL
NV-LB48	10-30V	Single color Dual color	11	150x3w 300x3W	IP67	Magnetic Mount Permanent Mount	5m Cables	R65 Class2, R10

05 / NOVA




• LED LIGHTBAR NV-LWAY30










- The led lightbar Can be built-in takedown light, alley light, traffic arrow light.
- Lifespan of up to 100,000 hours.
- He lightbar has Optional hand control boxes.
- Max 15.4 A draw.
- Five sizes for optional: 12",23", 30",40" and 48".
- can meet the requirements of different vehicles, like cars, vans, trucks, trailers, fire vehicles and ambulance vehicles.

ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	WIRE	APPROVAL
NV-Lway30	10-30V	Single color	25	60x3W	IP67	Magnetic Mount	3.5m cable	/

MINI BAR MN10







ITEM	VOLTAGE	COLOR	FLASH PATTERN	MOUNTING	IP	DIMENSION (L X W X H)	APPROVAL
MN10	10-30V	Amber Blue Red	10	Bolt Mount Magnetic Mount Bracket Mount	IP67	250x171x25mm	R65, R10 in pending



MULTI-WARNING LIGHT T43









T43

R65 Warning Strobe Light










- Input Voltage: 10~30V DC.
- LED: 1pcsx5W warning light, 2pcs 0.2W side marker.
- Certificates: R65 XA1, R10, R148.
- Dimensions: 18.5mm(Dia) x 20.5mm(H).
- Color Available: Amber / Blue / Red / White / Green.
- Waterproof: IP67.
- Function: Multi-function: Blue Warning light, Amber Warning light,
 Amber side marker, Red tail light, White position light.



	34.8mm	20.5mm
	15.5mm	
69.6mm		

ITEM	VOLTAGE	COLOR	FUNCTION	PATTERNS	LED	IP	MOUNTING	WIRE	APPROVAL
		Amber, Blue	Warning light only	14	1pcs 5W			25cm 4-core wires	ECE D/E VA1
T43	10-33V	Amber, Blue, White, Red	Warning light with marker light	Warning: 14 Marker light: Steady on	Warning: 1x5W Marker Light: 2x0.2W	IP67	Flush / Tube	25cm 5-core wires	ECE R65 XA1, XB1(4UNITS), R10, R148, SAE J595, J592, J2043,
		Amber, Red, White	Marker light only	Steady on	2x0.2W (Single color, Dual color, Triple color)			25cm 3-core wires	DOT





SILICONE BENDABLE LED LIGHTHEAD F6











ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	WIRE	APPROVAL
F6	10-20V DC	Single color	20	6x3W	IP68	3M Mount	20cm 4-core wires	R65/R10/
F6D	10-30V DC	Dual color	12	12x3W	1700	Bezel Mount	20cm 5-core wires	SAE

• SILICONE LENS WITH ALUMINUM BASE F6 PRO






Available in single color, dual color, and triple color














ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	WIRE	APPROVAL
F6 PRO		Single color	20	6x3W			20cm -5core wires	
F6D PRO	10-30V DC	Dual color	12	12x3W	IP68	Screw mount Rubber Pad	20cm -6core wires	R65 Class2, R10
F6T PRO		Triple color	12	18x3W		Mount	20cm 7-core wires	



QUAD COLOR LIGHTHEAD FL6










- 10-30V new lighthead.
- Unique and innovative streamlined design.
- Available in Single color, Dual color, Triple color and Quad color.
- Many mounting options for your reference, like 3M mount, screw mount and bracket mount.









ITEM	VOLTAGE	MAX POWER	LED	FLASH PATTERNS	DIMENSION (L X W X H)	ΙP	MOUNTING	APPROVAL
FL4		6W	Single: 4x3W Dual: 8x3W Tri: 12x3W Quad: 16x3W		94.4x25.6x10mm		Surface	ECE R65
FL6	10-30V	10W	Single: 6x3W Dual: 12x3W Tri: 18x3W Quad: 24x3W	single 20 / Dual , Tri and Ouad 12	130x25.6x10mm	IP67	Mounting, 3M Mounting, Bracket	Class 2 ECE R10 SAE J595
FL12		20W	Single: 12x3W Dual: 24x3W Tri: 36x3W Ouad: 48x3W	Quad 12	130x38x10mm		mount	Class 1

• SLIM LIGHTHEAD \$18









- Input Voltage: 10-30V.
- LED: 18x3W or 36x3W.
- Certificates: R65 XA1; R10.
- Color Available: Blue/Amber/ Red/ White/Green.
- Waterproof: IP67.
- Function: Single color or dual color.
- Slim design, can be fixed on the vehicle license plate or the bumper in front of vehicles.




- ـ	245	mm
=		1
<u></u>		
·		

ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	WIRE	APPROVAL
610	10.201/	Single color Dual color	10	18x3W	10/7	Permanent Mount	30cm	D/E D10
S18	10-30V			36x3W	IP67		wire	R65 and R10

• TRUE 180 DEGREE WIDE ANGLE STROBE LIGHT NR180





- Wide Angle XA1 and XB1
- Regular Angle R65 XA2 and XB2















ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	WIRE	APPROVAL
NR180		Single color	20	12x3W			20cm -5core wires	ECE R65 XA1,
NR180D	10-30V	Dual color	12	18x3W	IP67	3M Mount, Screw Mount, Offset Mount	20cm -6core wires	XB1, R10
NR180-P		Single/Dual	20/12	6/12x3W			20cm wires	ECE R65 XA2, XB2, R10


• MULTI-WARNING LIGHT NR180X2











- Double row warning light.
- Multi Warning light, warning light with marker light.
- Bespoke your own needs with us.
- Multiple mount options, surface mount or L bracket for your options.
- Wide beam angle 180-degree.
- 24Pcs or 36Pcs 3W LED for single color or dual color.
- 50% power steady on functions available.
- IP67 Standard waterproof.
- UV-resistant PC.



LED WARNING LIGHT O SERIES











- Ultra-slim body, only 7-7.5mm thickness.
- Finely designed polycarbonate lens shape produces uncompromising illumination.
- High-quality LEDs ensure consistent performance and extremely low current draw.
- Aluminum die-cast housing provides excellent heat dissipation.
- With variety bracket installation.
- Fully encapsulated for moisture, vibration and corrosion resistance.
- ECE R10(EMC),ECE R65 Class2 and SAE J595 Class1.





ITEM	VOLTAGE	COLOR	LED	PATTERNS	IP	MOUNTING	DIMENSION (L X W X H)	APPROVAL
О3		Single color/	3/6x3W	20/12			88x25x7.5mm	
04	10.20\/	Dual color	4/8x3W	20/12	IP67	Surface Mount, 3M Mount,	96x25x7.5mm	R65 Class2,
06	10-307	10-30V Single color / Dual color / Split color	6/12/18x3W	20/12	11 07	Bracket Mount	118x25x7mm	R10
O12			12x3W	20			111x35x7.5mm	


LED LIGHTHEAD

NL₆









28.5mr		20 5	
--------	--	------	--


ITEM	VOLTAGE	COLOR	POWER	FLASH PATTERN	IP	MOUNTING	WIRE	APPROVAL
NL6	10-33V	Single color	6x3W	20	IP67	Surface Mount	20cm wire	ECE R10, R65
N6	10 33 V	Multifunction Light	Warning:6x3W Mark:20x0.5W	10	IFO/	Surface Mount	Zociii wire	ECE R10, R65, R148


N6













LED LIGHTHEAD SH6

- © R65 for horizontal mount
- © R65 for vertical mount



Horizontal Mount





Vertical Mount





- Finely designed polycarbonate lens shape produces uncompromising illumination.
- high-quality LEDs ensure consistent performance and extremely low current draw.
- Aluminum die-cast housing provides excellent heat dissipation.
- Fully encapsulated for moisture, vibration and corrosion resistance.
- Faster and easier surface mounting via two screws.
- ECE R10(EMC), ECE R65 and SAE J595 Class1 Certified.
- With horizontal or vertical mount, R65 certificate separately.





ITEM	VOLTAGE	COLOR	POWER	FLASH PATTERN	IP	MOUNTING	WIRE	APPROVAL
SH6	10-33V	Single color	6x3W	20	IP67	Surface Mount	20cm wire	ECE R10, R65, SAE J595


LED LIGHTHEAD

T3









8	Ē	1		Ì
7	7.4	9	D	
25	CZ		\Box	Į


ITEM	VOLTAGE	COLOR	POWER	FLASH PATTERN	IP	MOUNTING	WIRE	APPROVAL
Т3	10.221/	Single color	3x3W	20	IP67	Surface Mount	20cm wire	ECE R10, R65
V6	10-33V	Single color Dual color	6x3W	20	IF O7	Surface Mount	Zociii wile	ECE R65

V6









19 / NOVA

• LED HIDEAWAY LIGHT HF6













- Multi-function strobe light.
- Amber warning light.
- ECE R65 Class1 or Class2 for your options.
- Integraded Amber side marker, Red tail light, white position light.





ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	WIRE	APPROVAL
HF6	10-30V	Single color	Warning: 19	Warning: 6pcs	IP67	Embedded	20cm 5-core	ECE R65 AND
0	10 00 0	onigie color	Steady On	Maker: 10pcs		Mount	wires	R10 IN PENDING

• BUILT-IN LED HIDEAWAY LIGHT


HT4











ITEM	VOLTAGE	COLOR	POWER	FLASH PATTERN	IP	MOUNTING	WIRE	APPROVAL
HT4	10.221/	Single color	4x3W	12 kinds/ Single	ID/7	Screw Mount or a Bezel	20cm 4-core wires	ECE R10,
HM4	10-33V	or Dual color	4x3W 8x3W	13 kinds/ Dual	IP67	is available	20cm wire	R65 TA1, TB1


HM4











LED HIDEAWAY LIGHT


H8












ITEM	VOLTAGE	COLOR	POWER	FLASH PATTERN	IP	MOUNTING	WIRE	APPROVAL
Н8	10-33V	Single color	8x3W	12 kinds/ Single	IP67	Screw Mount or a Bezel	20cm 4-core wires	ECE R10,
H12	10 33 V	or Dual color	12x3W	13 kinds/ Dual	IFO/	is available	20cm wire	R65 TA1, TB1


H12















LED HIDEAWAY LIGHT


HS4-S












ITEM	VOLTAGE	COLOR	POWER	FLASH PATTERN	IP	MOUNTING	WIRE	APPROVAL
HS4-S	10-30V	Single color	4x3W	12	IP67	Screw Mount,	20cm 4-core wires	ECE R10,
Н6	10 30 V	Single color	6x3W	12	IFO/	Bezel Mount	2.5m cables	R65

H6











LED BEACON

B16 PRO





Aluminum base equipped with the **best heat dissipation.**






Strong magnet mount can pass a 230km/h speed test.



Flexi DIN



Single Point



FLASH PATTERN ITEM VOLTAGE **COLOR** LED MOUNTING WIRE **APPROVAL** Magnetic Mount, B16 Pro Single color 18x3W 2.5m Cables Permanent R65 Class2, 10-33V 10 IP67 Mount, R10 30cm wires Dual color 36x3W BA18 Flexi DIN Mount

• LED BEACON BH18





Latest **optical design for** brighter and more even light distribution










Flexi DIN




Aluminum Base




Plastic Base









IT	тем	VOLTAGE	COLOR	LED	FLASH PATTERN	IP	MOUNTING	WIRE	APPROVAL
В	H18	10-33V	Single color or Dual color	18x3W	10	IP67	Magnetic Mount, Permanent Mount, Flexi DIN Mount	2.5m Cables or 30cm wires	R65 Class2, R10




• HPSC SERIES













- Provides a reliable, temporary vacuum mount, without drilling holes.
- Rubber vacuum pad will not mark or damage most surfaces.
- Attaches to flat or curved, smooth, nonporous surfaces.
- Red-line indicator warns user of any vacuum loss.
- Check valve allows re-pumping without lost of remaining vacuum.
- Lift tabs on vacuum pad edges permit instant release.
- Supplied with vacuum pad protector.




ITEM	PAD DIAMETER	LOADING CAPCITY	IRON PLATE DIAMETER	MATERIAL	SCREW
HPSC series	4.5″/118mm	Vertical>30kg Horizontal>50kg	140mm	Rubber& plastic& metal	M6 M8 G1/4" G3/8" Customizable Screw

MOTORCYCLE REAR LIGHT MP18









- The MP18 is the ultimate rear light solution.
- Offering adjustable height.
- A variety of lighting patterns to ensure maximum visibility.
- Its robust construction.
- Waterproof design makes it perfect for all weather conditions.

ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	DIMENSION (L X W X H)	APPROVAL
MP18	10-33V	Single color /Dual color	10	18x3W	IP67	Pole Mount	119 x 625x1020mm	R65 and R10



LED WARNING LIGHT


DF₆





- Silicone optical lens F6 inside of window pod.
- Certificates: R65 XA1, XB1; R10.
- Dimensions: 118mm x 76mm x29mm.
- Available: Blue/ Amber/ Red/ White/ Green.
- Waterproof: IP67.
- Function: Single color or Dual color.
- Window pods are available as spare parts.





ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	DIMENSION (L X W X H)	APPROVAL
DF6	10-33V	Single or Dual color	20 kinds/Single	6x3W 12x3W	ID47	3M mount	118x76.5x28.9mm	ECE R10,R65 TA1,TB1
DF12	10-337	Dual color	12 kinds/Dual	12x3W 24x3W	IP67	3M Mount	220 x 55 x 38mm	ECE R10,R65

DF12









- Silicone optical lens F6 inside of window pods.
- Dimension 220x55x38mm.
- Avaiable in single color and dual color.
- Adjustable angle: 0 ~ 75degree.
- 3M mounting options anti-collision design.
- ECE R65 Class1, R10.


LED WARNING LIGHT

D12











ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	CONTROLLER	APPROVAL
D12	10-22\/	Single or	20	12x3W	IP67	Suction cup	Cigarette plug/ Wire directly	R65 and R10,
DN6	10-33V Singi Dual o	Single or Dual color	olor 20	6x3W	IFO7		2.5m cables with Cig Plug	SAE















Mounting, Suction Cups

LED WARNING LIGHT DM4




The Max Adjustment Angle is 35°








- Input Voltage: 10~33V DC.
- With or without optical design.
- Max. Power: 12 W.
- Certificates: R65 XA1, XB1,R10.
- Dimensions: 40mm(Dia) x 21.8mm (H).
- Color Available: Blue/ Amber/ Red/ White/ Green
- Waterproof: IP67.
- Function: Single color or Dual color.





ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	WIRE	APPROVAL
DM4	10-33V	Single or Dual color	12 kinds/Single 13 kinds/Dual	4x3w 8x3W	IP67	3M mount	20cm wire	ECE R10,R65 TA1,TB1

LED WARNING LIGHT NW-FW






Automotive Lighting System

- A flexible and waterproof warning light designed to mark the position, but can be used anywhere on vehicles and machines.
- A simple and tool-free mounting with two cable ties that ensure a stable mounting.
- The available lengths are 19cm, 24cm, 34cm
- The standard voltage is 12V, can be customized to 10-30V.
- Available with Amber color, Blue color.
- Mode: Single flash, Traffic arrow function.









ITEM	VOLTAGE	COLOR	FLASH PATTERN	LENGTH	IP	MOUNTING
NW-FW	12V,10-30V	Amber Blue Red	Stead On/ Single flash/ Traffic arrow light	19cm, 24cm, 34cm	IP65	Cable Ties

31 / NOVA NOVA / 32




LED DIRECTIONAL LIGHT TN PRO SERIES










ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	WIRE	APPROVAL
TN	10.201/	Single color /Dual color	19 flash	214/	ID/7	Surface Mount	F0	D10 and D/F
TN Pro	10-30V	Single color/ Dual color/ Triple color	patterns	3W	IP67	L Bracket Mount	50cm wire	R10 and R65

LED DIRECTIONAL LIGHT TA SERIES










- Adopts high power LED as light source.
- Available in single dual and triple color.
- Waterproof interior or exterior mount.
- TA series comes with 3-wire cable(power, ground, pattern select).
- Bottom and rear T-slots allow for easy mounting via M3 bolts.
- Side aluminum housing for efficient heat dissipation prolongs lifespan.
- Sealed 06 heads for maximum reliability.



ITEM	VOLTAGE	COLOR	FLASH PATTERN	LED	IP	MOUNTING	WIRE	APPROVAL
TA	10-30V	Single color /Dual color	2-4modules:20 >4modules:31	3W	IP67	Permanent Mount, Bracket Mount	5m wire	R65 and R10



CONTROLLER SC7X







100mm

- All-in-one controller, Max load is 40A.
- 6 Programmable momentary or ON/OFF buttons.
- With selectable icon stickers to clearly label your switch.
- With master and slave function, one button can control a group of switches.
- 6 outputs, 2 outputs Max 10A, 4 outputs Max 5A.
- Double color back lights with auto dimming function.
- Mutiple mounting options for your reference.
- ECE R10 approved.
- Universal compatibility.
- With over-temperature protection, short circuit protection and reverse polarity protection.





• MINI CONTROLLER SC5X











- All-in-one controller with integrated relay.
- Universal compatibility.
- Over-temperature protection and short circuit protection
 4 Programmable momentary or ON/OFF buttons.
- 18 selectable icon stickers to clearly label your panel.
- 4 Outputs, each outputs 5A.
- 1/4" thread stand screw hole for bracket mount.
- ECE R10 approved.





ITEM	VOLTAGE	MAX OUTPUT	FUSE	MOUNTING	WIRE	DIMENSION (L X W X H)	APPROVAL
SC5X	10-30V	20A	5A for each switch	3M Mount, Bracket Mount	30cm Cables	62x62x25mm	R10




BLINK DEVICE & LED FLASHER

AC-R2A



- 10-30V blink device for side marker lamps.
- Max Current 2A.
- IP68, waterproof relay for side markers. Side markers flash synchronously with D.I.
- According to ECE R48, Rev. 6.
- Applications: Heavy duty trucks and trailers, transportation vehicles.
- Can be customized.





ITEM	VOLTAGE	MAX OUTPUT	MOUNTING	IP	WIRES	DIMENSION	APPROVAL
AC-R2A	10-30V	2A	2A Screw Mount IP68 30cm Cables		75x41x22mm	R10	
AC-FL	10 30 V	2x5A	Screw Mount	11 00	Joenn Cables	69x67x22mm	/



- 10-30V (Vin=Vout).
- 18 selectable flash patterns, with dim, cruise and mode functions.
- Slim design shape.

• 2 x 5A outputs.

- The flasher unit can drive many more LED directional lightheads.
- Can sync or alternating the modules.



- 4	Red 15-30VDC leput
	Block END legat
	Rive: Output to LEE modules White: Output to LEE modules
	Yollanc Pattern Select

Quad Alt (125 fpm) R65

Double Alt (125 fpm) R65

Single Alt (125 fpm) R65

Quad Alt (180 fpm) R65

Double Alt (180 fpm) R65

Single Alt (180 fpm) R65

Quad Alt (75 fpm)

Red -	10~30VDC Input	1	Quad Sim (125 fpm) R65	10
Red		2	Double Sim (125 fpm) R65	11
Black —	GND Input			
Yellow -	Change Flash Pattern	3	Single Sim (125 fpm) R65	12
reliow	Change Flash Fallern	4	Quad Sim (180 fpm) R65	13
Grey -	Cruise Mode	5	Double Sim (180 fpm) R65	14
Green —	— Dim Mode	3	Double Silli (100 ipill) 1003	14
		6	Single Sim (180 fpm) R65	15
White —	GND Output	7	Quad Sim (75 fpm)	16
Blue -	V1+ Output(5A)	8	Double Sim (75 fpm)	17
Orange -	V2+ Output(5A)	9	Single Sim (75 fpm)	18
9				

LED ROCK LIGHT RKL











- The led rock light is available with single color, dual color and RGB LED Rock Lights Kit version.
- 12V or 10-30V, 12V version can be built-in with a switch and dimming function. 10-30V rock light without switch.
- Ultra High Intensity 3pcs 3W LED, extremely efficient.
- High Impact UV-coated Polycarbonate.
- Beam Angle Flood: 120°.
- Rubber Mounts included for installation.
- Aluminum housing with powder coating.





ITEM	VOLTAGE	COLOR	HOUSING	LED	IP	SWITCH	DIMENSION (L X W X H)	BRACKET
RKL	12V or 10-30V	Single/ dual/ triple color	Black or White	3x2.6W	IP68/ IP69K	With or not	74x38x13mm	Silicone Pad

37/ NOVA NOVA / 38




LED ROAD FLARES NA-RW01



- 6-pack kit includes a carrying case and a charging station.
- Rechargeable LED road flare with strong magnetism.
- 1000mAh Lithium-ion battery provides long battery life.
- The LED road flare case includes a 12V accessory adapter plug and a 120V AC wall charger.
- 360° beam angle with 9 selectable light pattern.








ITEM	BATTERY	COLOR	FLASH PATTERN	PLUG	IP	DIMENSION
NA-RW01	1000mAh	Amber, Blue, Red Yellow, Green, Black	9	12V adapter or 110V/220V charger	IP67	373x350x76mm

SIRENS

NV-SR100RD





ITEM	VOLTAGE	POWER	IMPEDANCE	IMPEDANCE FUNCTION		LIGHT SWITCHES	APPROVAL
NV-SR100RD	12/24\/	Wrecker, Project		200x108x48mm	3	CE, RoHS	
NV-SR100HD	12/24V	100W	8Ω /11Ω	Wail, Yelp Hi-Lo, PHSR Stop	180x177x82mm	2	/

NV-SR100HD









NV-SR100AD	
LxWxH(MM)	194x155x57
VOLTAGE	DC12V
POWER	100W/200W
IMPEDANCE	8Ω/11Ω
DISTORTION/SOUND	Yelp,Hi-lo,Wail-1,Wail-2,Manual
LIGHT SWITCHES	2



NV-SR100-9	
LxWxH(MM)	166x150x146
FRENQUENCY	400-4000Hz
POWER	100W
IMPEDANCE	$4\Omega/6\Omega/8\Omega$
DISTORTION/SOUND	≤5%
SOUND COMPRESSION LEVEL	120-130db



NV-SR100VD	
LxWxH(MM)	120x123x54
VOLTAGE	DC12V
POWER	100W
IMPEDANCE	8Ω/11Ω
DISTORTION/SOUND	Horn, Siren, Yelp, Wail-2, Wail, Hi-Lo, Wail-3
LIGHT SWITCHES	2



NV-SP200	
LxWxH(MM)	215x189x118
FRENQUENCY	300-4600Hz
POWER	200W
IMPEDANCE	4Ω/6Ω/8Ω
DISTORTION/SOUND	≤5%
SOUND COMPRESSION LEVEL	120-130db



NV-SP100-2	
LxWxH(MM)	182x135x175
FRENQUENCY	400-4000Hz
POWER	100W
IMPEDANCE	Ω8
DISTORTION/SOUND	≤5%
SOUND COMPRESSION LEVEL	120-130db



NV-S100-2	
LxWxH(MM)	192x172x87
FRENQUENCY	400-4000Hz
POWER	100W
IMPEDANCE	8Ω/11Ω
DISTORTION/SOUND	≤5%
SOUND COMPRESSION LEVEL	120-130db




NV-SP100-1	
LxWxH(MM)	205x173x132
FRENQUENCY	400-4000Hz
POWER	100W/200W
IMPEDANCE	8Ω
DISTORTION/SOUND	≤5%
SOUND COMPRESSION LEVEL	120-130db



NV-SP100-3B	
LxWxH(MM)	145x138x52
FRENQUENCY	400-4000Hz
POWER	100W
IMPEDANCE	4Ω/6Ω/8Ω/11Ω
DISTORTION/SOUND	≤5%
SOUND COMPRESSION LEVEL	120-130db





AUXILIARY LIGHT

Designed to boost visibility interior and exterior light in your vehicle for a safe working environment, our auxiliary light range offers powerful, waterproof and robust solutions.

LED STRIP LIGHT NSXZ SERIES










- 10-30V wide voltage led strip light
- Available with silver housing or black housing
- High lumen design, with higher brightness
- 20cm, 30cm, 50cm, 70cm and 100cm for your options



ITEM	VOLTAGE	LIGHT COLOR	IP	LUMENS	CABLE	MOUNTING	DIMENSION
NSXZ50	10-30V	4500K 6000K	IP67	800lm	1m or 2m cable	Clip Mount Scew Mount	500x17.5x7mm




LED STRIP LIGHT



CLEAR SILICONE WATERPROOF
OR MILKY SILICONE WATERPROOF





ITEM	VOLTAGE	WATTAGE	LIGHT COLOR	IP	LUMINOUS	CABLE	LED	MOUNTING	DIMENSION
NSLP30		Max 4W			400lm				304x20x10mm
NSLP50	10-30V	Max 6W	4500K 5000K 6000K	IP67	600lm	1m or 2m Cables	SMD2835	Clip Mount	504x20x10mm
NSLP100		Max 12W			1200lm				1004x20x10mm

LED STRIP LIGHT













ITEM	VOLTAGE	WATTAGE	COLOR TEMP	IP	LUMINOUS	CABLE	MOUNTING	DIMENSION (L X W X H)
NSLD20		3W	4000K		300lm			200x16.5x9mm
NSLD50	10-16V	8W	5000K	IP67	800lm	1m or 2m	Clip Mount Magnetic Mount	500x16.5x9mm
NSLD100	or 24-30V	17W	6000K		1700lm	Cables	Screw Mount	1000x16.5x9mm
NSLD150		25W	OUUK		2500lm			15000x16.5x9mm




LED STRIP LIGHT

NSVP SERIES







ITEM	VOLTAGE	WATTAGE	COLOR TEMP	IP	LUMINOUS	CABLE	MOUNTING	DIMENSION (L X W X H)
NSVP30		4Max7.2W	4500K	ID / 7	420lm	1m or 2m Cables	Clip Mount, Screw Mount	300x19x12m
NSVP50	10-16V	Max 7.2W	5000k		800lm			500x19x12m
NSVP100	or 24-30V	Max 14.5W		IP67	1500lm			1000x19x12m
NSVP150		Max 21.6W	6000k		2200lm			1500x19x12m

CARAVAN LIGHT

NA-ILS01R












- Available with single color or dual color.
- Black or White Plastic housing.
- IP67, suitable for indoor and outdoor use.

- Voltage: 12VDC and 10-30VDC.
- Touch switch, sensor switch or without switch for your options.

NA-ILS02







- Interior light, better for Bus.
- Voltage: 12V.
- Black or White Plastic housing.

47 / NOVA

Automotive Lighting System




LED AUXILIARY LIGHT

NW-L40



- 40pcs 1W LED, 2500lm, powerful and more brighter.
- 10-30V Multi Voltage, suitable for buses and heavy-duty vehicles.
- Can be customized in red, black, or white housings.
- R10 approval





NA-L51




- 45 degree scene light, 51pcs 1W LED, 1080lm.
- 12V or 10-30V Multi Voltage, widely application.
- Available with single color, dual color and triple color.
- Flood Beam, 45° angle with 120° spread.
- UV-coated polycarbonate.











CARAVAN LIGHT

NW-LC


- Size: 250mm, 300mm, 360mm, 550mm.
- Voltage: 10-30V.
- Black or White housing.
- Clear or frosted cover.

NSLN50




- Screw mounting, 3M sticker mounting, Clips mounting for your options.
- ON/OFF Button with dimming function.
- Bespoke your lengths.
- Soft lighting, no dizzy.
- Available with single color or dual color.


NA-C20



- LED interior light, auxiliary white light.
- Size: 260mm, 410mm, 770mm.
- Voltage: 12V or 5V.
- Touch switch & Built-in dimming function.
- Available with Single color or Dual color.









49 / NOVA





LED WORK LIGHT

Vehicle lighting plays a vital role in ensuring safety on the roads.


We offer durable, heavy-duty led work light,

enhance safety to all kinds of vehicles.

LED WORK LIGHT

NW-C48






- Flood Offroad Led Light, the durable LED work light is waterproof and shock-resistant.
- Super Bright -4 inch square Led trailers Lights with 16pcsx3w High intensity led.
- High Performance Our 5.5 inch LED pods have a lifetime of about 50,000 hours lifetime with IP67 rated (waterproof, dustproof, shockproof).
- Dustproof/shockproof, anti-corrosion.
- This LED work light is suitable for jeep, reversing, off-road vehicle, automobile, motorcycle, ATV, UTV,
- SUV, truck, trailer, forklift, train, boat, bus, street car, sand track and other lights.

ITEM	VOLTAGE	MAX POWER	COLOR TEMP	IP	LUMINOUS	LED	WORKING TEMPEATURE	DIMENSION (L X W X H)
NW-C48	10-32V	48W	6000K	IP68	3600lm	16x3W	-40-80°C	108x108x56mm
NW-C36	10-32V	36W	5000K	1100	1800lm	9x4W	-40-00 C	100x100x56mm

NW-C36










LED WORK LIGHT

NW-EW36



- Flood light NW-EW36 is designed for all 12V/24V vehicles.
- They are used as driving lights for on-road/off-road trucks.
- Aluminum housing guarantees excellent heat dissipation.
- The updated sealing design ensures it's IP68 waterproof.
- High transparency PC lens and silica gel cable ensure the pod lights work perfectly from -40 to 80 Celsius degrees on automobiles and heavy-duties.



ITEM	VOLTAGE	WATTAGE	COLOR TEMP	IP	LUMINOUS	LED	WORKING TEMPEATURE	DIMENSION (L X W X H)
NW-EW36		36W	4000K	IP68	3200lm	18x2W	-40-+85°C	102x125x40mm
NW-E40	10-32V	40W	6000K	IP69K	4800lm	4x10W	-40-80°C	105x95x75mm

NW-E40



- Heated lens (Snow- melting) and dimmable functions are optional.
- Self-owned triangle type anti-vibration bracket, it guarantees uniform illumination of the work area for tractors and large machines.
- High rigidity tempered glass len, better weather and shock resistance.


LED WORK LIGHT

NW-C1



Automotive Lighting System

- All new screwless and glueless watertight design.
- Small size, high power, cost-effective.
- Racing style design perfect match motorcycle, ATV/UTV, Skidoo, e-bike, etc.




ITEM	VOLTAGE	MAX POWER	COLOR TEMP	IP	LUMINOUS	LED	WORKING TEMPEATURE	DIMENSION (L X W X H)
NW-C1	10-32V	10W	6000K IP6	IP68	900lm	10W	-40-80°C	62x62x75mm
NW-CB1		15W/10W	8000K	IP68	1650lm	15W/10W	-40-80 C	60x60x79mm

NW-CB1











53 / NOVA NOVA / **54**




FORKLIFT LIGHT

NW-L30








NW-L20








NW-U20








NW-U5









ITEM	VOLTAGE	POWER	LED COLOR	IP	DIMENSION (L X W X H)	APPROVAL
NW-L30	0.4401/	30W		IP67	134X65X64.5mm	CE/RoHs/E-Mark
NW-L20	9-110V	20W	Red, Blue, Green		98x63x75mm	
NW-U20	9-80V Red	20W			128.5x92x120mm	
NW-U5	9-110V Blue /Green	5W			72x112x72mm	

LED WORK LIGHT

NW-FM50









NW-FM60









NW-FM90







ITEM	VOLTAGE	MAX POWER	COLOR TEMP	IΡ	LUMINOUS	LED	WORKING TEMPEATURE	DIMENSION (L X W X H)
NW-FM50	4	48W	5300K-5700K	IP68	4250lm	5x10W	-40-80°C	108x108x56mm
NW-FM60	10-32V	36W			5100lm	6X10W		144x95x83mm
NW-FM90					8360lm	9X10W		163x110x87.5mm





LED SIGNAL LIGHT

As a specialist in the field of LED vehicle lighting,
we have the knowledge and skills to provide customised
applications in addition to standard lighting.
We strive to provide customised solutions to
your commercial vehicles, trailers and trucks.

WIRELESS TRAILER LIGHT NS-T01 SERIES





WIRELESS TRAILER LIGHT KITS





- 12V or 12-24V
- Wire or wireless trailer light for your options
- Suitable for trailers or truck vehicles
- EU Plug wiring configurations and vehicles fitted with a 7-pin or 13-pin plug towing trailers.
- European Plug or Australia plug for your options.
- Functions: brake: lights, rear turn signal lights, rear position lights, license plate lights, and return reflectors
- CE,RF.EMc, Rohs, Heaithy report compliant.

57 / NOVA



LED SIDE MARKER NS-TL011









ITEM	FUNCTION	LED/POWER	IP	VOLTAGE	DIMENSION (L X W X H)	CERTIIFCATION
NS-TL011T	Tail/Stop/Reverse	Tail:1.2W	IP67			E9 approval
NS-TL011E	Tail/Stop/Turn	Stop:2.2W Dynamic Indicator:4.4w		10-30V	140mm diameter	
NS-TL011U	Tail/Stop/Turn	Reverse:3.5W				

• LED SIDE MARKER NS-TL012











- Multifunctional Rear Combination Ligh
- 10-30V
- Functions:Dynamic indicator/Stop/Rear position/
- License/Reflector/Fog/Reverse
- IP67
- ECE R3, R6, R7,R23,R38, R10
- Dimension,305x140x35mm







ITEM	VOLTAGE	FUNCTION	MOUNT	IP	CERTIIFCATION	DIMENSION
NS-TL012	100MA	STT,reversing fog,licence light	Screw Mount	IP67	ECE R6,R7, R3,R38,R10	305x140x35mm

• LED SIDE MARKER

M5









M3









M43








SD6




Single color or Dual color






SPARE PARTS
































ECE

The United Nations Economic Commission for Europe (UNECE:) Transport Division has been providing secretariat services to the World Forum for Harmonization of Vehicle Regulations for more than 50 years. ECE is a quality mark that shows that your vehicle or product complies with EC guidelines. The Ec directives can be understood as the legislation of the European Union.

ECE R65

ECE R65 is a developed stand ard in the EU that affects warning ard emergency light. This covers se.veral different characteristics that a warning, light has. Such as light image, color, intensity and frequency. This applies to 360° radiant light èis well as directed warning light.

For approval, all minimum requirements must be met. This approval is a requirement for products for use as warning light on vehicles.

Class | ECE R65 is also divided into two different classes. Class I is the standard for night mode.

Class II is the standard for day- and night mode. The equipment needs to be able to switch in order to meet the reduirements.

R10

ECE-R 10 is a type of approval for electrical systems on vehicles and means that the lighting does not cause interference with other electrical equipment.

SAE

SAE International (SAE), formerly the Society of Automotive Engineers, is a professional organization for mobility engineering professionals in the aerospace, automotive, and commercial vehicle industries. The Society is a standards development organization for the engineering of powered vehicles of all kinds, including cars, trucks, boats, aircraft, and others. The SAE standards are mainly used in the Us and canada and do not recognize ECE approvals

IP67

IP stands for 'international Protection Rating, and indicates whether a product is dust and waterproof. P67 means completely dust-tight and immersion-proof to a depth of 1 meter for up to 30 minutes.











IP68

IP stands for 'international Protection Rating' and indicates whether a product is dust and waterproof. IP68 means completely dustproof and waterproof to depths pf more than 1 meter and longer than 30 minutes.

IP69K

IP stands for 'international Protection Rating' and indicates whether a product is dust and waterproof. IP69K means completely dust-tight, waterproof, moisture-proof and high-pressure spray resistant.

CISPR 25

CISPR 25 Class5 is a classification for components designed to have the lowest level of electromagnetic emissions so that systems function properly without interference.

R7

ECE-R7 is a regulation for daytilme running lights. EcE-R7 certified lighting may be officially used as daytime running lights if installed and connected correctly.

R112

ECE-R112 is a regulation for high beams. ECE-R112 certified lighting may officially be used as high beam if properly installed and connected.

R148

ECE-R148 is an overarching new regulation and follows, among others, R7. ECE-R148 certified lighting may be officially used as daytime running lights if installed and connected correctly.

R149

ECE-R149 is an overarching new, regulation and follows, among others, R112 ECE-R149 certified lighting may officially be used as hight beam if installed and connected correctly.













